



## LED Flood Light



UNIT: cd — V 0.0082 PLAN, 90.9 — H 0.0082 PLAN, 89.2

NFL258S 300W 5700K



10W=60  
30/50W=80  
100/150W=150  
200/300W=180

	A	B	C	D	E	F
10W	131	116	176	140	39	φ8.5
30W	176	160	219	183	42	φ8.5
50W	203	186	283	236	57	φ8.5
100/150W	265	245	368	320	64	φ11
200W	356	336	435	380	72	φ11
300W	427	387	503	455	78	φ14

### TECHNICAL DETAILS

- 10W, 30W, 50W, 300W Voltage as 100-240V
- 100W, 150W, 200W Voltage as 220-240V
- IK06 rating
- CRI>80
- IP65 rating
- 2.5KV surge protection
- Operating temperatures: -20-45°C
- 50,000 hours of lifetime

### APPLICATIONS

Landscape / Plaza / Architecture / Car Parks

### FEATURES

- Die-cast aluminum housing
- Powder coated surface treatment
- Driver included
- Tempered glass front cover and dark gray body

Model	Power(W)	Lumens	Size/mm	Color Temp	CRI	PF
NFL258S	10	1300	176*131*39	3000K / 5700K	80	0.9
NFL258S	30	3600	219*176*42	3000K / 5700K	80	0.9
NFL258S	50	6500	282*203*57	3000K / 5700K	80	0.95
NFL258S	100	14000	368*265*64	3000K / 5700K	80	0.95
NFL258S	150	21000	435*356*72	3000K / 5700K	80	0.95
NFL258S	200	26000	435*356*72	3000K / 5700K	80	0.95
NFL258S	300	38000	503*387*78	3000K / 5700K	80	0.95